PROFESSIONAL TECHNICIANS

Stable product quality inspection





PROFESSION EXPERINCE

We are a professional manufacturer and supplier of automotive coatings. We have more than 10 years of history and rich experience in the coatings industry.

"Chengmao Technology" was established in 2007, specializing in the production of automotive paint, top paint, primer, metallic color, pearl color, express dry varnish, high gloss thick film varnish, anti-yellow curing agent, advanced diluent, 1K / 2K primer, advertising special alloy paint, industrial paint.

Our products have been favored by domestic and foreign customers for many years. Most of the raw materials used by our company are selected from BASF, Bayer, etc., after strict and serious screening, the entire production process has gone through strict and serious testing, focusing on the formulation research and development, production and sales,OEM and marketing of automotive coatings.

Advantage

SOFTWARE

Professional computer software technology







QUALITY CONTROL

We are very experienced in the paint business with a history more than 10 years. We have introduced a lot of advanced paint production equipment, testing equipment, to produce a variety of paints with high-end and stable quality, such as car repair paint, industrial paint, metal paint for machines and so on.

FINISHED PAINT FORMULAS PROGRAM

chengmao auto paint finished paint formulas system, for you to improve the finished paint preparing efficiency










FABRIC TESTING

Please make inquiry and send us your brand name and logo, and we will design the package cans and boxes for you.





CARPAINT

Have a massive library of color recipes and continuously update the professional color palette
With and system support, it is easy to achieve the formula color easy construction and high quality
Quality, time saving and high efficiency, strong hiding power, lasting color, high gloss






TopLiking AG-818

- HS Dazzling Clearcoat
- Good Weather Resistance
- Non-Polishing
- O Complete Spray
- 1 Durable hard and beautiful 2 Perfect paint film effect 3 Leading nanotechnology





ADVANTAGED TECHNOLOGY







ADVANTAGED TECHNOLOGY



TopLiking

[White Pearls]
Special Clearcoat

- Non-Polishing
- Ory Quickly
- Good Weather Resistance

① Durable hard and beautiful ② Perfect paint film effect ③ Quality assurance



ADVANTAGED TECHNOLOGY







ADVANTAGED TECHNOLOGY



TopLiking

- Non-Polishing
- O Dry Quickly
- **Fast Dry Clearcoat**
- O Good Weather Resistance

1 Durable hard and beautiful 2 Perfect paint film effect 3 Thirteen minutes is dry



ADVANTAGED TECHNOLIY

- 1. Drying fast (15°C touch drying time is 10-15 minutes).
- 2. Polishing time can be shortened to 3-4 hours at 20°C, which is greatly improved Customer delivery time.
- 3. Resistance to weather is very good, high gloss varnish suitable for local spray paint



- TopLiking Poly-Putty Base
 - **Easy To Apply**
 - **Easy To Grind**
 - **Strong Adhesion**
 - 1) quality assurance 2 stable performance
- 3 curing fast 4 durable



Substrate And Preparation



This product has very good adhesion to different substrates. Can be applied on the following materials; Bare iron and aluminum after degreasing and polishing. Galvanized steel after degreasing and polishing. Polished fiberglass (fiberglass reinforced plastic), polyester putty, industrial primers in good condition and old coatings. Warning: Do not apply sheet metal ash directly to active primers, single-component acrylic and nitrocellulose products.





¬ Product Introduction



Spraying special atomized ash is made of air-dry unsaturated polyester resin, modifier, pigment, ultrafine filler, Anti-settling materials and special additives are dispersed and mixed at high speed. When used, the special liquid curing agent is evenly mixed at the ratio of 100:2-3 It can be sprayed like spray paint





TopLiking **Multirole Fibre Putty**

- **Strong Adhesion**
- **Easy To Grind**
- **Good Flexibility**
- 1) Quality assurance 2 stable performance 3 fast curing 4 durable







- 1. After removing oil stains from bare iron, steel plate and iron plate, grind P80# sandpaper lightly
- 2. After removing oil stains from aluminum, aluminum alloy and galvanized sheet, P180# sandpaper is lightly ground
- 3. After removing oil pollution and cleaning, P180# sandpaper is lightly ground







Product Introduction

Spraying special atomized ash is made of air-dry unsaturated polyester resin, modifier, pigment, ultrafine filler, Anti-settling materials and special additives are dispersed and mixed at high speed. When used, the special liquid curing agent is evenly mixed at the ratio of 100:2-3 It can be sprayed like spray paint